

## **Quality Frame Tents for Rental and Commercial Industries**

CALL US: 800-997-8368

EMAIL: sales@centraltent.com

Georgia Location: 889 Industrial Blvd Ringgold, GA 30736

Texas Location: 5911 Hamblen Dr, Humble, TX 77396, United States



15x30 Standard Frame Tent			
Qty		FITTINGS	Part#
4	Corner		C1001
2	3 Way Crown		C1004
2	Side Tee Joint		C1003
1	Ridge Slide Tee 2"		C1010-2
1	15 Ft. Cable		CB15X
38	Canopy Pins		P102
Qty	Size	Poles	Color
7	14'-4"	Spreader	Red
4	10'-6"	Hip Rafter	Green
2	7'-8"	Rafter	Black
6	7'-8"	Legs	Black

## 15x30 STANDARD HIP END - FRAME TENT

## **INSTRUCTIONS:**

- 1. Lay out four(4) corner fittings, two (2) tee fillings, and six (6) (red 14'4") spreader pipes and form a perimeter frame. Assemble and insert 16p nails.
- 2. Put one (1) (red 14' 4") spreader pipe and two (2) 3-way crown fittings into the center of the frame. Slide two (2)adjustable slide fittings to the center of the spreader pipe.
- 3. On one end, insert one (1) (green 10'6") hip rafter into corner fitting and nail. Then insert the opposite end of the hip rafter into the 3-way crown fitting and nail. Insert one

end of another hip rafter into the same 3-way fitting and nail. Then insert the opposite end into the corner fitting and nail.

- 4. Insert one end of the center spreader into the assembled 3-way crown fitting and nail.
- 5. Insert one end of the side rafter(orange 7'7") into side tee fitting and nail. Insert the opposite end into the slide fitting on the center spreader and nai. Repeat on the opposite side.
- 6. Repeat steps 3 and 4 to complete the remaining end of the frame.
- 7. Place the canopy over the frame and pull tight. Secure canopy to frame with buckle straps, tightening corner buckles first.
- 8. Raise one side of the canopy, insert leg pipes (black 7'8") into the corner, and tee fittings and nails.
- 9. Raise the opposite side of the canopy and install the remaining legs.
- 10. The canopy and frame can now be tied down.

Caution, tie down only at corner or tee fittings. Do not tie to spreader pipe as they may bend.